### §420.44

(2) If the permittee demonstrates to the satisfaction of the permitting authority that safety considerations prevent attainment of these limitations, the permitting authority may establish alternative limitations on a best professional judgment basis.

[47 FR 23284, May 27, 1982, as amended at 67 FR 64267, Oct. 17, 2002]

## § 420.44 New source performance standards (NSPS).

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

- (a) Basic oxygen furnace steelmaking—semi-wet; and electric arc furnace steelmaking—semi-wet. No discharge of process wastewater pollutants to navigable waters.
- (b) Basic oxygen furnace steelmaking—wet-suppressed combustion.

#### SUBPART D

	New source performance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0146 0.000188 0.000282 (¹)	0.00522 0.0000626 0.0000939 (1)

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

(c) Basic oxygen furnace steelmaking—wet open combustion; and electric arc furnace steelmaking—wet.

#### SUBPART D

	New source perform- ance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS Lead Zinc pH	0.0321 0.000413 0.000620 (¹)	0.0115 0.000138 0.000207 (1)

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

[47 FR 23284, May 27, 1982, as amended at 67 FR 64267, Oct. 17, 2002]

# § 420.45 Pretreatment standards for existing sources (PSES).

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

- (a) Electric arc furnace steelmaking—semi-wet. No discharge of process wastewater pollutants to navigable waters.
- (b) Basic oxygen furnace steelmaking—wet-suppressed combustion.

#### SUBPART D

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
LeadZinc	0.000188 0.000282	0.0000626 0.0000939

(c) Basic oxygen furnace steelmaking—wet open combustion; and electric arc furnace steelmaking—wet.

#### SUBPART D

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
LeadZinc	0.000413 0.000620	0.000138 0.000207

- (d) Basic oxygen furnace steelmaking—semi-wet. (1) No discharge of process wastewater pollutants to navigable waters.
- (2) If the permittee demonstrates to the satisfaction of the pretreatment control authority that safety considerations prevent attainment of these limitations, the pretreatment control authority may establish alternative limitations on a best professional judgment basis.

 $[47\ FR\ 23284,\ May\ 27,\ 1982,\ as\ amended\ at\ 67\ FR\ 64267,\ Oct.\ 17,\ 2002]$